# **DATA SHEET**

# сор. 1595

# 33VDC POWER SUPPLY UNIT FOR IKALL ENTRANCE PANEL

Power supply unit with 110-230V primary and 33Vdc 500 mA continuous output, and 1.2A inrush current for external unit with IKALL entrance panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).



#### Compatibility

Simplebus Top system:	Yes	
Simplebus Color system:	Yes	
Simplebus 2 system:	Yes	

## **Mounting/Installation**

Wall-mounted:	Yes
Surface-mounted:	Yes
DIN rail mounted:	Yes
DIN modules (no.):	4

#### Audio/video specifications

Audio system:	Yes	
Audio/video system:	Yes	

## Connectivity

Stabilised output:	Yes
Parallelable power supply outputs:	No

## **Technical properties**

Temperature range:	0 / 40

#### **Electrical specifications**

AC supply voltage:	110 / 240 V
Switching power supply:	Yes
Direct voltage output A (V):	33
Maximum current absorption (mA):	300



The technical specifications are subject to variations without warning

# **DATA SHEET**

Single pack depth (mm):

	Maximum power delivered:	18 W
Genera	l info	
	EAN product code:	8023903211979
	Product height (mm):	85
	Product width (mm):	60
	Product depth (mm):	35
Packag	ling	
	Single pack height (mm):	216
	Single pack width (mm):	126

38

