



6741W

MINI HANDSFREE WIFI MONITOR, SBTOP



Wall-mounted hands-free monitor with full-duplex audio and 4.3" / 16:9 colour screen. It is equipped with a Wi-Fi port to allows calls forwarding to mobile devices. Allows brightness control, plus adjustment of the ringtone volume, which can be customised by choosing one of several different melodies.

Equipped as standard with 8 sensitive touch back-lit controls for audio activation, door-opening, self-ignition, switchboard call, privacy service and LED signalling for the door status. Manages floor door calls as standard.

Complete with 2 x 8-position dip-switch for user code programming and button programming. The wall-mounting backplate and riser distribution terminal art. 1214/2C are included. The monitor can only be used in 2-wire system Simplebus Top. Dimensions: 4.53"x6.3"x0.87".

AWARDS



CERTIFICATIONS





6741W

MINI HANDSFREE WIFI MONITOR, SBTOP

MAIN FEATURES

Audio/video system:	Yes
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	Yes
Type of display:	LCD
Display size (inch):	4,3" 16:9
OSD display:	Yes
Display resolution HxV (inch):	480x272
B/W or color display:	Color
Product color:	White
Sensitive Touch technology:	Yes
Total buttons:	8
LED signaling (no.):	4
Wi-Fi Port:	Yes
Comaptibility with Video Entry Comelit App:	Yes

FUNCTIONS

Actuator control function:	Yes
Self-ignition:	Yes
Switchboard call function:	Yes
Priority calls:	Yes
Intercom function:	Yes
Selective intercom call:	Yes
Call to multiple addresses:	Yes
Call forwarding:	Yes
Privacy function:	Yes
Doctor:	Yes
Floor door call function:	Yes
Electronic bell:	Yes
Customisable ringtone:	Yes
Privacy conversation function:	Yes
Key button function:	Yes

HARDWARE SPECIFICATIONS

Removable terminals:	Yes
Type of finish:	Plastic

SETTINGS

Loudspeaker volume control:	Yes
-----------------------------	-----



6741W

MINI HANDSFREE WIFI MONITOR, SBTOP

SETTINGS

Display brightness control:	Yes
-----------------------------	-----

GENERAL DATA

Product height (inch):	6.3
Product width (inch):	4.53
Product depth (inch):	0.87

COMPATIBILITY

Simplebus Top audio/video system:	Yes
-----------------------------------	-----

TECHNICAL CHARACTERISTICS

Power supply voltage:	22 ÷ 28
Absorption in stand-by (mA):	70
Absorption during call (mA):	180
Absorption during communication (mA):	300
IP protection rating:	IP30
Operating temperature (°F):	41 ÷ 104
RH max operating humidity (%):	25 ÷ 75
Clamps:	L L CFP1 CFP2



6741W

MINI HANDSFREE WIFI MONITOR, SBTOP

ACCESSORIES



6711WV

ADAPTER PLATE FOR MINI HANDSFREE

Adapter plate to finish the installation of the Mini Handsfree monitor in case of replacement of flush-mounted or wall-mounted Planux, Smart and Icona monitors. White color. Dimensions: 170x220x3 mm.



6710

BACKPLATE AND DISTRIBUTION TERMINAL FOR MINI MONITOR

Wall-mounting or residential series box backplate for MINI monitor, /BM versions with handset featuring magnetic induction for hearing aid wearers. Also includes riser distribution terminal Art. 1214/2C. Dimensions 145x100x4 mm.



6720

BRCKT FOR ROUTING EXT. CABLES. HANDSFREE MINI MON.

Wall support bracket for handsfree Mini monitor allowing thru-routing of external cables. Dimensions:106.3x149.60x19mm.



6732A

DESK BASE FOR HANDS-FREE MINI MONITOR. SBTOP

Desk base installation accessory for hands-free Mini monitor in Simplebus Top system.