

Concentrating on audio since 1988

DSP6011 Ceiling Speaker



Features

- ➤ It is made of high quality anti-UV engineering plastic, long-term durability and fashionable;
- Fence structure can be avoid damaging speaker from roaches, rats etc.;
- ➤ Long life, sounds clear and sonorousness;
- ➤ Different input voltage (70V/100V) can be chosen for different public address wires;
- Frequency response 90Hz 20kHz, maximum SPL. 103±2dB,High sensitivity 95±2dB, distortion<1.5%;
- Weight 0.9kg, equipped with clamps for installation.

Description

The DSP6011 is a surface mount ceiling speaker with a 70v/100v transformer built in. The 70v/100v transmission is realized in a high-voltage, low-current mode, which makes longer distance transmission and parallel connection of multiple loudspeakers possible.

It's easy to install with strong clip, and made of high-quality engineering plastic, which is durable, non-deformable and non-fading. It is an ideal choice for these places, such as schools, gymnasiums, square halls, parks, parking lots, railway stations, airports, villa communities and mall supermarkets, etc.



Concentrating on audio since 1988

Specification

Model	DSP6011
Frequency Range (-10 dB)	90Hz-20,000Hz
Sensitivity	95dB ±2dB
Max SPL	103dB±2dB
Input Voltage	70V/100V optional
RMS	6W
Dimension	Ф 185mm×74mm
Weight	0.9kg