

# DHI-IVD5148-3I

## 48CH 1U INTELLIGENT VIDEO DEVICE



 Xinghan  WizMind

Launched by Dahua Technology, Dahua WizMind is a full portfolio of solutions composed of project-oriented products including IPC, IVSS, NVR, PTZ, XVR, Thermal and software platform which adopts industry-leading deep learning algorithms. Focusing on customer's requirements, WizMind provides precise, reliable and comprehensive AI solutions for verticals.

### Series Overview

Dahua IVD is an AI edge computing device that combines traditional video management with intelligent video analytics. It provides real-time AI monitoring and high-speed data processing on-site. With its built-in deep learning module, this series offers high-precision AI functions including human face recognition, video metadata, and industrial algorithms, making it widely applicable to various industries and the perfect solution for upgrading traditional CCTV systems in the most cost-effective way.

### Functions

#### Face Detection

Empowered by deep-learning algorithms, the device supports face detection, tracking, and capture, and outputs the best face snapshots. It supports analysis of up to 6 face attributes.

#### Face Recognition

Supports recording faces with incredible accuracy through metadata and real-time cross-check to recognize faces with target features. With Regular and Stranger face modes, the device triggers a wide variety of alarm actions to suit different situations.

#### Video Metadata

Metadata is the information on the features and attributes that is extracted from target objects which can be used for data retrieval. Currently, there are 4 main kinds of metadata in the security industry: Human face, human body, and motor vehicle and non-motor vehicle metadata.

- 64-bit High-performance multi-core processor
- Max 48-ch IP camera inputs
- Max 256/256/256 Mbps incoming/recording/outgoing bandwidth
- Up to 48-channel AI IVS
- Up to 48-channel face recognition with normal IPC
- Up to 32-channel face recognition with face detection IPC
- Up to 48-channel video metadata
- Up to 48-channel AcuPick with normal IPC
- Up to 100 face databases with 500,000 face pictures in total
- Up to 48-channel 1080p intelligent video compression
- 1 SATA bay, Max.20 TB
- 2 HDMI/1 VGA video output



#### IVS

Within specified restricted areas, intelligent detections are carried out, such as tripwire, intrusion, parking, people loitering and gathering. Driven by deep learning algorithms, IVS can provide precise person and vehicle classification detection, and accurately trigger alarms based on object types (pedestrians and vehicles), to greatly reduce the generation of false alarms. In addition, some basic functions including tripwire and intrusion are also referred to as perimeter protection.

#### AcuPick

This industry-leading search technology effectively utilizes both front-end and back-end intelligence to help with searching through massive video data to quickly and conveniently locate targets with greater precision.

#### Intelligent Video Compression

Dahua intelligent compression adopts the advanced self-adaptive bit rate control algorithm. It supports live view, playback and download by transmitting compressed streams through the network, to provide high-quality videos and reduce storage and network transmission costs.

#### WizSeek

Powered by Xinghan large-scale AI model, WizSeek enables natural-language video search for human, vehicle, object, and event with high accuracy, while reducing investigation time by transforming manual reviews into instant results.

## Technical Specification

### System

Main Processor	64-bit high-performance multi-core processor
Operating System	Embedded Linux OS
Operating Interface	Web (PCAPP); local GUI
AI Card	3, AI card mode is switchable

### AI Applications

AI by Camera	Face detection; face recognition; video metadata (human; vehicle; non-motor vehicle); IVS; license plate comparison; tripwire people counting; regional people counting; abnormal number of people in queue; smoking detection; call detection; face & body detection
AI by Recorder	Face detection; face recognition; video metadata (human; vehicle; non-motor vehicle); IVS
AcuPick	1. AI by Recorder: Supports 48-channel 2 MP or 48-channel 4 MP resolution(16-channel for each AI card). 2. AI by Camera: Supports 32-channel 2 MP or 32-channel 4 MP resolution

### Multimodal Large Models

WizSeek	<p>AI by Recorder:</p> <ul style="list-style-type: none"> <li>• 32-ch 2 MP or 32-ch 4 MP or 16-ch 8 MP WizSeek with AcuPick IP camera (Min. 1 AI card for WizSeek modeling),</li> <li>• 32-ch 2 MP or 32-ch 4 MP or 16-ch 8 MP WizSeek with normal IP camera (2 AI cards for AcuPick by recorder, 1 AI card for WizSeek modeling)</li> <li>• Each AI card for WizSeek modeling can analyze 16 targets/s</li> </ul> <p>Search Language: English,Traditional Chinese</p>
---------	--

### Face Detection

Face Detection	<p>1. AI by Recorder: Supports 48-channel 2 MP or 48-channel 4 MP resolution(16-channel for each AI card)</p> <p>2. AI by Camera: Supports 32-channel 2 MP or 32-channel 4 MP resolution</p> <p>3. Supports 6 properties: Gender, age, glasses, expression, face mask, and beard</p>
----------------	--

### Search by Image

Search by Image	Search by image in the face database, search by face or human body images, and 1:1 face recognition.
-----------------	--

### Face Recognition

Face Database Capacity	<p>1.100 human face databases with 500,000 face pictures in total</p> <p>2. 5 passerby databases with 500,000 face pictures in total</p> <p>The human face database and the passerby database share the total capacity and number of face images.</p>
Face Recognition	<p>1. AI by Recorder: 48-channel 2 MP or 48-channel 4 MP with normal IP camera(16-channel for each AI card); 32-channel 2 MP or 32-channel 4 MP with face detection IP camera (Totally 32 × 2 MP or 32 × 4 MP face pictures analyzed per second);</p> <p>2. AI by Camera: 32-channel 2 MP or 32-channel 4 MP with face recognition IP camera;</p> <p>3. Supports entries frequency alarm</p>

## Vehicle License Plate Comparison

License Plate Database Capacity	<p>1. 50 plate databases with 300,000 plate numbers in total</p> <p>2. Supports allowlist and blocklist</p>
Vehicle License Plate Comparison	Supports 32-channel 2 MP or 32-channel 4 MP resolution with ITC

### Video Metadata

Video Metadata	<p>1. AI by Recorder: Supports 48-channel 2 MP or 48-channel 4 MP resolution (16-channel for each AI card)</p> <p>2. AI by Camera: Supports 32-channel 2 MP or 32-channel 4 MP resolution</p> <p>3. Object type: Human body: Gender, age, sleeves length, top color, bottom type, bottom color, bag, rain coat, umbrella, hat, hairstyle, direction, hold a baby, face mask Vehicle: Plate No., vehicle type, vehicle color, plate color, logo, calling, seatbelt, ornament Non-motorized Vehicle: Non-motor vehicle type, non-motor vehicle color, number of passengers, umbrella, rain coat, bag , sleeve, length, top color, hat, hair style, face mask</p> <p>4. Supports match or mismatch attributes alarm for video metadata</p>
----------------	---

### IVS Analytics

IVS	<p>1. AI by Recorder: Supports 48-channel 2 MP or 48-channel 4 MP resolution(16-channel for each AI card)</p> <p>2. AI by Camera: Supports 32-channel 2 MP or 32-channel 4 MP resolution</p> <p>3. Rules: AI by Recorder: climbing detection, tripwire, intrusion, parking detection, crowd gathering, stay detection and loitering detection AI by Camera: tripwire, intrusion, abandoned object, missing object, fast moving, crowd gathering, loitering, parking and fence-crossing</p>
-----	--

### Video Diagnosis

Video Diagnosis	<p>1. Supports 1-channel tour detection</p> <p>2. Supports 12 detection items: blurry video, low contrast, video tampering, video jitter, image freeze, overexposure detection, video loss, noise detection, scene changing, static noise, interference fringe and color cast</p>
-----------------	---

### Intelligent Video Compression

Intelligent Video Compression	<p>1. Compressed preview, playback and download of source stream on the platform.</p> <p>2. Supports origin/compression dual stream live view and storage.</p> <p>3. Supports compressing a variety of third-party code streams (ONVIF/RTSP).</p> <p>4. Compression Resolution: 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/1.3 MP/720p/D1.</p> <p>5. Each AI card supports up to 2-channel 12 MP/4-channel 8 MP/ 6-channel 5 MP/8-channel 4 MP/16-channel 2 MP and below.</p>
-------------------------------	---


### Industrial Algorithms

Industrial Algorithms	The industrial algorithm is an optional installment.
-----------------------	--

Work Behavior Analysis	1. AI by Recorder: Without large model (by default): 24-channel 2 MP/4 MP/8 MP (8-channel for each AI card) With large model(optional): 12-channel 2 MP/4 MP/8 MP (4-channel for each AI card) 2. Rules: AI by Recorder: calling, using mobile phone, sleeping while on duty, leave post detection, smoking and abnormal number of people	Network Mode	Multiple-address mode;Load balance;Fault-tolerance;Link aggregation
			Recording Playback
PPE Detection	1. AI by Recorder: 24-channel 2 MP/4 MP/8 MP (8-channel for each AI card) 2. Rules: AI by Recorder: hat/safety helmet detection, Balacalva, workwear detection (detect by color attributes or registered database), face mask detection, goggles detection, seatbelt detection, safety vest detection, shoes detection, gloves detection, mask detection, exposed hair detection and arm band detection	Multi-channel Playback	Max. 16-channel playback
		Record Mode	Search auto; manual; video detection; IO alarm; thermal imaging; intelligent event; all record file
Smart Object Detection	1. AI by Recorder: 24-channel 2 MP/4 MP/8 MP (8-channel for each AI card) 2. Rules: AI by Recorder: smart missing object and smart abandoned object 3. Object Type: non-motor vehicles, luggage, bags and boxes	Storage Method	Internal HDD
		Backup Method	HDD, peripheral USB storage device
People Behavior Analysis	1. AI by Recorder: Without large model (by default): 24-channel 2 MP/4 MP/8 MP (8-channel for each AI card) With large model(optional): 6-channel 2 MP/4 MP/8 MP (2-channel for each AI card) 2. Rules: AI by Recorder: fighting detection, fall detection, running detection and tailing detection	Playback Function	1. Play; Pause; Stop; Fast forward; Fast backward; Reverse play; Frame by frame; 2. Full-screen; Backup (clip and file); Snapshot; Digital zoom; Audio on and off
		Storage	
Audio and Video	Record Management	Record Management	Supports record control (continuous, event-based, scheduled, scheduled & event-based)
		Alarm	
Access Channel	General Alarm	General Alarm	Motion detection; tampering; IPC external alarm; heat alarm; temperature alarm; temperature difference alarm; hot spot alarm; cold spot alarm
		Anomaly Alarm	IPC offline alarm; storage error; HDD full; IP conflict; MAC conflict; login lock; AI module temperature alarm; AI module offline; fan malfunction; no HDD; power exception
Network Bandwidth	Alarm Linkage	Alarm Linkage	Record; snapshot (full image); alarm uploading; remote device alarm output; camera audio; buzzer; log; preset; email, and smart tracking. Disarming alarm linkage action by period or one-click sync disarm config with channels
		Port	
Resolution	Audio Input	Audio Input	1 channel
		Audio Output	1 channel
Decoding Capability	Alarm Input	Alarm Input	4 channels
		Alarm Output	2 channels
Video Output	Disk Interface	Disk Interface	1 slot, SATA. Max.20 TB/HDD
		RS-232	1 port
Multi-screen Display	RS-485	RS-485	1 port
		USB	4 ports. 2 USB2.0 ports at the front panel and 2 USB3.0 ports at the rear panel.
Third-party Camera Access	HDMI	HDMI	2 ports. Port 1 supports 4K output.
		VGA	1 port
Compression Standard	Network Port	Network Port	2 RJ-45 10/100/1000Mbps self-adaptive Ethernet ports
		Power	Single supply
Video Compression	General	Disk Bay	1
		Form Factor	1U
Audio Compression	Power Supply	Power Supply	12 VDC,5 A
		Power Consumption	28 W (without HDD, idling) 35 W(all HDDs connected)
Network	Network Protocol	Network Protocol	HTTP;HTTPS;TCP/ IP;IPv4;RTSP;UDP;SMTP;NTP;DHCP;DNS;DDNS;P2P;IPv6; UPnP;SNMP
		Mobile Phone Access	DMSS
Interoperability	Interoperability	Interoperability	ONVIF (Profile S, T and G); CGI; SDK
		Browser	Chrome; PCAPP; IE9 or higher; Firefox

Fan	Intelligent speed regulation fan
Net Weight	1.75 kg (3.86 lb)
Gross Weight	2.78 kg (6.13 lb)
Product Dimensions	Chassis: 304 mm × 223.8 mm × 43.5 mm (11.97" × 8.11" × 1.71") (W × D × H)
Packaging Dimensions	With packaging: 399 mm × 304 mm × 133 mm (15.71" × 11.97" × 23.58") (W × D × H)
Operating Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Operating Humidity	10%–90% (RH), non-condensing
Operating Altitude	≤5,000 m (16,404.20 ft)
Installation	Desktop; Rack
Certifications	CE-LVD : EN 62368-1 CE-EMC : EN IEC 61000-3-2 , EN 61000-3-3 , EN 55032 , EN 50130-4 , EN 55035

### Dimensions (mm[inch])



### Ordering Information

Type	Model	Description
INTELLIGENT VIDEO DEVICE	DHI-IVD5148-3I	48CH 1U INTELLIGENT VIDEO DEVICE

### Panels

