

# High PoE Midspan



### **Features**

- > Support PoE for High PoE 60W high power consumption speed dome
- > Indicator status: power (normal power on), PoE (normal power supply)
- > Cooperate with PoE Extender (PFT1300), able to cascade level 2 PoE Extender, connect to 3 IPC (power consumption <=8W), max transmission distance 300m
- > Installation mode: wall mount

# **Technical Specifications**

Model	PFT1200
Ethernet port	1*10/100/1000 Base-T、
	1*10/100/1000 Base-T( PoE power supply)
POE Power	Support high PoE 60W
Supply	
Indicator	Power indicator, PoE status indicator
Exchange mode	Store & forward
Application	10%-90%
Humidity	
High&Low	- 30℃~65℃
temperature	
Weight	390g



### **PFT1200**

$\begin{array}{ c c }\hline \text{Dimension(W} \times \\ \text{D} \times \text{H)} \end{array}$	150mm×70mm×39mm
---	-----------------

### Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883 Fax: +86-571-87688815

Email:overseas@dahuatech.com

www.dahuatech.com

\*Design and specifications are subject to change without notice.

© 2012 Dahua Technology Co., Ltd.