

# DHI-TPC-BF5401-T

## Thermal Network Bullet Camera



- Vanadium oxide uncooled focal plane detector.
- AI functions: heat detection, tripwire, intrusion, and human/vehicle classification.
- Wide input voltage 12 VDC  $\pm$  20%, and PoE.
- IP67 rated.

Featuring thermal channel, Thermal Network Bullet Camera offers various AI functions such as heat detection, tripwire, intrusion, and human/vehicle classification. The camera is widely applied in outdoor scenes of the medium-distance perimeter protection and heat detection.

### Technical Specification

#### Thermal

Detector Type	Vanadium oxide uncooled focal plane detector
Effective Pixels	400 (H) $\times$ 300 (V)
Pixel Pitch	17 $\mu$ m
Spectral Range	8 $\mu$ m–14 $\mu$ m
Sensitivity (NETD)	$\leq$ 35 mK (@f/1.0)
Focus Control	Fixed-focal
Aperture	F1.0
Focal Length	7.5 mm; 13 mm; 25 mm; 35 mm
Field of View	7.5mm: H:53.5°; V:39.5° 13 mm: H:30.4°; V: 22.5° 25 mm: H:15.5°; V:11.6° 35 mm: H:11.1°; V:8.3°
Close Focus Distance	7.5 mm: 1 m (3.28 ft) 13 mm: 3 m (9.84 ft) 25 mm: 10 m (32.81 ft) 35 mm: 20 m (65.62 ft)
Digital Detail Enhancement (DDE)	Yes
Thermal AGC	Auto/Manual
Thermal Noise Reduction	2D NR/3D NR
Image Flip	180°
Color Palettes	18 (white hot/black hot/fusion/rainbow/golden autumn/midday/iron red/amber/jade/sunset/icefire/painting/pomegranate/emerald /spring/summer/autumn/winter)
Temperature Measurement Range	Low temperature mode: –20 °C (–4 °F) to +150 °C (+302 °F) High temperature mode: 0 °C (+34 °F) to +550 °C (+1022 °F) Auto mode

#### Temperature Measurement Mode

Spot: 12  
Line: 12  
Area: 12  
Supports 12 rules simultaneously

#### Audio and Video

Video Compression	H.265; H.264; H.264H; H.264B; MJPEG
Resolution	Thermal: Main stream: 1280 $\times$ 1024; 1280 $\times$ 960; 1280 $\times$ 720; 400 $\times$ 300; 1280 $\times$ 960 (default) Sub stream: 640 $\times$ 512; 640 $\times$ 480; 400 $\times$ 300; 400 $\times$ 300 (default)
Video Frame Rate	Thermal (50 Hz): Main stream: 1 fps–25 fps, 25 fps by default Sub stream: 1 fps–25 fps, 15 fps by default Thermal (60 Hz): Main stream: 1 fps–30 fps, 30 fps by default Sub stream: 1 fps–30 fps, 15 fps by default
Audio Compression	G.711a; G.711mu; AAC; PCM
Image Encoding Format	JPEG

#### Function

Network Protocol	HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; SNMP; QoS; UPnP; NTP
Storage	FTP; Micro SD card (optional)
Interoperability	ONVIF; CGI; DaHua SDK
Browser	IE; Firefox; Chrome
User/Host	Up to 20 (total bandwidth: 64 MB)
Security	Authorized username and password; attached MAC address; encrypted HTTPS; IEEE 802.1x; controlled network access
User Management	Up to 20 users; supports multi-level user permissions (2 levels): management group and user group
Malfunction Detection	Network disconnection detection; IP conflict detection; memory card state detection; memory space detection

Micro SD Card (Max.)	512 GB
Intelligence	
Heat Detection	Yes
Cold/Hot Spot Trace	Yes
Perimeter Protection	Yes. Supports tripwire and intrusion.
Target Distinction	Human/Vehicle Classification

Port	
Analog Output	1 × CVBS output; BNC port
Network Port	1 × RJ-45 (10/100 Base-T)
Alarm Input	2
Alarm Output	2
Audio Input	1
Audio Output	1
RS-485	1

Power	
Power Supply	12 VDC ± 20%, PoE (802.3af), ePoE
Power Consumption	Basic: 5.0 W (12 VDC); 5.5 W (PoE) Max.: 13 W (heater on ,12 VDC); 14 W (heater on, PoE)
ePoE	Yes

Environment	
Operating Temperature	−30 °C to +70 °C (−22 °F to +158 °F)
Operating Humidity	≤95%
Storage Temperature	−30 °C to +70 °C (−40 °F to +158 °F)

Physical Characteristics	
Protection	IP67
Reliability	Surge protection: 6 kV Air discharge: 15 kV Contact discharge: 8 kV

Structure	
Product Dimensions	291 mm × 103 mm × 97 mm (11.46" × 4.06" × 3.82") (L × W × H)
Packaging Dimensions	Package: 365 mm × 175 mm × 176 mm (14.37" × 6.89" × 6.93") (L × W × H) Protection box: 902 mm × 380 mm × 380 mm (35.51" × 14.96" × 14.96") (L × W × H)
Net Weight	≤1.4 kg (3.09 lb)
Gross Weight	≤1.9 kg (4.19 lb)
Bracket	Included

Certification	
Certifications	CE; FCC

Temperature Measurement Distance		
Focal Length	Max. Distance	Min. Distance
7.5 mm	5 m (16.40 ft)	1 m (3.28 ft)

13 mm	11 m (36.09 ft)	2 m (6.56 ft)
25 mm	21 m (68.90 ft)	4 m (13.12 ft)
35 mm	29.4 m (96.46 ft)	6 m (19.69 ft)
Note: The table displays the measured distances obtained from using the target size 0.1 m x 0.1 m for testing in an environment where the temperature is 23 °C and the relative humidity is below 60%. The table is for reference only. The distances within it are subject to actual conditions including atmospheric conditions, target size, the installation site, and more.		

DRI Distance			
Focal Length	Detection Distance <sup>①</sup>	Recognition Distance <sup>②</sup>	Identification Distance <sup>③</sup>
7.5 mm	Vehicle: 676 m (2,217.85 ft); Human: 221 m (725.07 ft)	Vehicle: 169 m (554.46 ft); Human: 55 m (180.45 ft)	Vehicle: 85 m (278.87 ft); Human: 28 m (91.86 ft)
13 mm	Vehicle: 1,173 m (3,848.43 ft); Human: 382 m (1,253.28 ft)	Vehicle: 293 m (961.29 ft); Human: 96 m (314.96 ft)	Vehicle: 147 m (482.28 ft); Human: 48 m (157.48 ft)
25 mm	Vehicle: 2,255 m (7,398.29 ft); Human: 735 m (2,411.42 ft)	Vehicle: 564 m (1,850.39 ft); Human: 184 m (603.67 ft)	Vehicle: 282 m (925.20 ft); Human: 92 m (301.84 ft)
35 mm	Vehicle: 3,157 m (10,357.61 ft); Human: 1,029 m (3,375.98 ft)	Vehicle: 789 m (2,588.58 ft); Human: 257 m (843.18 ft)	Vehicle: 395 m (1,295.93 ft); Human: 129 m (423.23 ft)
① Detection Distance: Detects objects, but cannot recognize their characteristics (objects must cover more than 1.5 pixels of the image). ② Recognition Distance: Classifies objects into general categories, such as human, vehicle (the object must cover more than 6 pixels of the image). ③ Identification Distance: Classifies objects into specific categories based on their characteristics, such as engineering truck, car (the object must cover more than 12 pixels of the image).			
Note: The table is the standard theoretical calculation and is for reference only. The distances within it are subject to actual conditions including atmospheric conditions, target size, the installation site, and more. For the intelligent detection distance, refer to the table of Perimeter Protection Distance (IVS Distance) above.			

Ordering Information		
Type	Model	Description
Security	DHI-TPC-BF5401-TB7	Thermal: 7.5 mm
	DHI-TPC-BF5401-TB13	Thermal: 13 mm
	DHI-TPC-BF5401-TB25	Thermal: 25 mm
	DHI-TPC-BF5401-TB35	Thermal: 35 mm
Accessories (Optional)	PFA121 + PFA151	Corner Mount
	PFA121	Junction Mount
	PFA152-E + PFA121	Vertical Pole Mount

Accessories

Optional:



PFA121 + PFA151  
Corner Mount



PFA121  
Junction Mount



PFA152-E + PFA121  
Vertical Pole Mount



PFM320D  
Power Adapter

Corner Mount	Junction Mount	Vertical Pole Mount

Dimensions (mm[inch])

