


ERBU

E-EFS-0402-60-M-120


4-Port PoE Managed Switch



Panels



Dimensions mm (inch)



Technical Specification

Hardware

Ethernet Port	2*1000 Base-X 1*10/100/1000 Base-T(Hi-PoE/PoE+/PoE) 3*10/100 Base-T (PoE+/PoE)
PoE Power Consumption	Port 1, 2, 3 ≤30W Port 4 ≤60W Total ≤ 120W
PoE Protocol	PoE(802.3af), PoE+(802.3at), Hi-PoE
Switching Capacity	6.8G
Packet Forwarding Rate	4.91Mpps
Packet Buffer Memory	1Mb
Application Humidity	10%~90%
Power	48~57 VDC
Lightning Protection	Common Mode 4KV Differential Mode 2KV
Working Temperature	-30°C~65°C
Weight	480g
Dimension(W×D×H)	150mm×100mm×30mm
System	Username / password: admin/(empty) IP Address :192.168.1.110/24
PoE Budget	120W
MAC Table Size	8K
VLAN	802.1Q Standard VLAN
Port Mirroring	Support many-to-one port mirroring
Flow Control	Support half-duplex based on back pressure type control Support full duplex based on PAUSE frame
Network Management	WEB, SNMP V1/V2C
Ring Network	Support Spanning Tree, STP/RSTP Support Loop Detection
PoE Management	Support PoE power consumption, PoE on/off of IPC configuration, power down when exceeding the value of overload power