

# SLIM-S-DUAL-PRO BUS

**SLIM-S-DUAL-PRO BUS** is an indoor ceiling motion detector from the SLIM LINE series, designed for **surface-mounted ceiling installation**. The detector can be connected to the RS communication bus of a SATEL alarm control panel supporting bus-connected devices.

The device is also available in a version designed for recessed ceiling mounting (**SLIM-R-DUAL-PRO BUS**).

- compliant with the **EN 50131 Grade 3** requirements
- active IR anti-masking compliant with **EN 50131-2-4 for Grade 3**
- motion detection using a passive infrared (PIR) sensor and a microwave (MW) sensor
- maximum detection area:
  - $\varnothing$  6 m / 28 m<sup>2</sup> – mounting height 2,4 m
  - $\varnothing$  10 m / 79 m<sup>2</sup> – mounting height 3,5 m
- adjustable detection sensitivity for both sensors
- digital motion detection algorithm for both sensors
- digital temperature compensation
- RS communication bus
- settings configuration via the RS bus
- firmware update via the RS bus
- built-in temperature sensor (measurement range: -10°C to +55°C)
- supervision of the motion detection circuit
- 12 V DC power supply ( $\pm 15\%$ )
- power supply monitoring
- tamper protection against enclosure opening and removal from the mounting surface
- surface-mounted ceiling installation



Supply voltage	12 V DC
Detected target velocity	0,2...3 m/s
Operating temperature range	-10°C...+55°C
Recommended mounting height	2,4...3,5 m
Standby mode current consumption	16 mA
Max. current consumption	45 mA
Weight	117 g
Maximum humidity	93 $\pm$ 3%
Dimensions	$\varnothing$ 120 x 37 mm
Environmental class according to EN50130-5	II
Alarm signaling time	2 s
Complied with standards	EN 50131-1, EN 50131-2-4, EN 50130-4, EN 50130-5
Security grade according to EN50131-2-4	Grade 3
Warm-up period	30 s