

ODC-41030



Vandalproof IR Dome Camera

IR LED: Φ 5X36PCS IR LED working distance: 30M

Lens: 4-9mm Manual Zoom Lens USD2 extra for 2.8-

Dimension: Φ 131 x 93(H) mm Weight:800g



Model		ODC-41030		
IMAGE DEVICE		Color 1/3" SONY Effio-E, 700TV Lines Low Illumination, ATR,OSD(DNR, PM, MD)		
SCANNING SYSTEM		NTSC/PAL		
NUMBER OF PIXELS		NTSC:1020(H)×508(V) PAL:1020(H)×596(V)		
SYNC. SYSTEM		INTERNAL		
RESOLUTION		700 TV LINE		
MINIMUM ILLUMINATION		0.001 Lux/ F2.0		
S/N RATIO		52dB(AGC off)		
SUPPLY VOLTAGE		DC 12V		
GAMMA CORRECTION		0,45		
GAIN CONTROL		AUTO		
EXPOSURE		AUTO ELECTRONIC SHUTTER 1/60(1/50)~1/100000		
OSD SET	LENS	MANUAL		
		AUTO	TYPE:DC/VIDEO MODE:CLOSE/AUTO/OPEN SPEED:0-255	
		SHUTTER/AGC	AUTO	HIGH LUMINANCE MODE:SHUT+AUTO IRIS/AUTO IRIS BRIGHTNESS:0-255 LOW LUMINANCE MODE:OFF/AGC BRIGHTNESS: ×0.25, ×0.5, ×0.75, ×1
			MANUAL	MODE:SHUT+AGC SPEED:1/60,1/120,1/250,1/500,1/1000,1/2000,1/4000,1/10000
	WHITE BAL		MANUAL	AGC:6,12,18,24,30,36,42,44.8 SPEED:0-255 DELAY CNT:0-255 ATW FRAME: ×0.5, ×1.0, ×1.5, ×2.0 ENVIRONMENT:INDOOR/OUTDOOR
			CR/PUSH LOCK	
		VIDEO OUTPUT		1.0 Vp-p COMPOSITE VIDEO. 75(OHM) LOAD
		POWER CONSUMPTION		150mA(+/-10%)
	OPERATION TEMP.		From -10°C TO 55°C	
	LENS TYPE		Optional	
	DIMENSION		38x38mm	